

CRACK REPAIR KIT



Super Stone® Crack Repair Kit is an easy to apply and complete system that provides flawless, long-lasting crack repairs. Crack repair material can be feather-edged to zero, resulting in seamless, durable repairs that are invisible after applying decorative top coat.

RECOMMENDED USAGE

For use with or without fabric as a concrete patch or may also be used as a flexible waterproof coating for above or below grade cementitious surfaces such as concrete, masonry, stucco foundations, block, cement ponds, or CBS walls.

- Interior and Exterior
- Spalled and Cracked Concrete
- Pedestrian and Vehicular Traffic Surfaces
- Horizontal and Vertical Applications
- Concrete and Masonry Resurfacing Projects

COVERAGE

100 Linear Feet Per 4 Gallons
3 ft² per bag at 1/2" thick
6 ft² per bag at 1/4" thick
12 ft² per bag at 1/8" thick
25 ft² per bag at 1/16" thick

DRY TIME

Approximately 4-24 hours depending upon location, temperature and humidity.

SURFACE PREPARATION

Remove any spalling, loose, or deteriorated cementitious surfaces. Use a high-pressure water cleaner or sandblast. (2500 PSI) Surface must be firm, free of dust, dirt, oil, debris or moisture.

APPLICATION

Mixing Instructions

Smooth or textured finish: Mix thoroughly with 16 oz of water and 4 lbs of mix.

Knock down finish: Use less water. Start with 12 oz and add an ounce at a time until the desired consistency is obtained.

Mix no more than 16 oz of water per kit. Dry times vary dependent upon temperature, humidity, and mixing water temperature. After application protect from freezing and moisture water for at least 24 hours. Air and surface temperature of the substrate will affect the working time and method of curing needed.

Once Mixed

Only mix material needed and apply mixture to cleaned patch area with a margin trowel or spackle knife at 1/16" thickness. Let the material set for approximately 5 minutes depending upon the temperature. Cooler temperatures will take longer to set. Warm or hot temperatures will set quicker. Dip the tile sponge into the bucket of cool water and wring out so that the sponge is moist but not soaked. Use the sponge to blend the edges and smooth the first coat. Mix the remainder of the patch kit. Dip a long-bristled paint brush into the patch kit and flick the material onto the patch area. Wait about 5 minutes' and use a pool trowel to knock down the drops of material flicked from the brush. One pass is all that is needed. The area should be completely dried within a few hours. Use the edge of the trowel to scrape any nips or burs from the patched area. A grinding stone may also be used. The deck is now ready to be resealed once it is fully cleaned and dried.

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended. Avoid breathing vapor for prolonged periods of time and use gloves to avoid repeated contact with the skin. In case of fire, use foam, dry chemical or Carbon Dioxide.

Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes and seek immediate medical attention. **Skin**-- Wash the affected area thoroughly with soap and water. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If symptoms persist or develop, seek medical attention. **Ingestion**-- Do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water.

Limited Warranty: *Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits.*

FOR PROFESSIONAL USE

WARNING! HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. OVEREXPOSURE MAY CAUSE SKIN IRRITATION, SERIOUS EYE IRRITATION, RESPIRATORY IRRITATION, ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED USE, SUSPECTED OF CAUSING CANCER.

