

PAVER KOTE SEALER



Super Stone® Paver Kote Sealer is a deep penetrating solvent-based acrylic sealer designed for, but not limited to brick pavers. It has the ability to enhance and protect pavers, decorative concrete, natural stone overlay systems and all masonry surfaces. Super Stone® Paver Kote Sealer is a complete non-yellowing coating that allows superior resistance to automotive grease, oil, and dirt.

RECOMMENDED USAGE

- Brick Pavers
- Unpainted/Unsealed Concrete
- Super Surface® Overlay System
- Super Tex Wet & Ready®
- Natural Stone

ADVANTAGES

- Non-Yellowing
- Acrylic Finish
- Durable & Aesthetically Appealing

COVERAGE

1 Gallon Covers Approximately 150 ft²
5 Gallons Cover Approximately 750 ft²

DRY TIME

24 hours for foot traffic
72 hours for vehicular traffic

SURFACE PREPARATION

Before applying Super Stone® Paver Kote Sealer, make sure all contaminants and bond-inhibiting materials are removed from the surface such as old paint. Use Super Stone® Cleaner/ Degreaser to remove dirt, oil, grease, and other petroleum based contaminants. Use Super Stone® Strip It Off to remove old acrylics, epoxies, and polyurethanes. Failure to remove contaminants will result in adhesion loss, reduced durability, or peeling. After cleaning, the surface must be allowed to dry completely or moisture may become trapped beneath the sealer resulting in peeling. Pavers must be fully cured.

APPLICATION

Super Stone® Paver Kote Sealer may be applied with a brush, a ¼"-¾" nap solvent resistant roller cover, or a sprayer resistant to solvents. For best results, apply sealer in a thin, even coat when surface and ambient temperatures are above 50° F and below 90° F. The first coat of Super Stone® Paver Kote Sealer acts as a primer for the second coat. Allow the first coat to dry 2-4 hours depending on humidity tack-free before applying the second coat. Two thin coats are recommended. Prevent over application by measuring the area to be sealed and the corresponding volume of product required based on the coverage rate. Application too heavily, in too many successive coats, in multiple coats over time can cause whitening, peeling, and ultimate failure of the product. Do not allow the product to puddle or collect in joints when applying. If whitening, peeling, or failure of the product occurs use Super Stone® Strip-It-Off to remove product and reapply. Clean tools with Super Stone® Solvent.

LIMITATIONS

Super Stone® Paver Kote Sealer should not be used in areas subject to:

- Water Submersion
- Significant Chemical Exposure
- Concentrated Abrasion/Scratching
- Metal Wheel Traffic
- Roadways

or as a waterproofing material or below-grade surfaces such as:

- Swimming Pools
- Concrete Ponds

Make sure that a test for compatibility is performed when sealing surfaces that have been treated with a curing membrane or sealer other than Super Stone® Paver Kote Sealer. Due to the degree of varying surfaces, application of Super Stone® Paver Kote Sealer is at the installer's discretion.

APPLICABLE STANDARDS

Resin	100% Acrylic
Solvent	Solvent Naphtha Light Aromatic
Total Non-Volatile	29.8%
Flash Point	80.6°F

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended. Avoid breathing vapor for prolonged periods of time and use gloves to avoid repeated contact with the skin. Do not use near fire or flame. Do not smoke during application and drying periods. In case of fire, use CO2 or dry chemical extinguisher. Do not use water spray.

Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes and seek immediate medical attention. **Skin**-- Wash the affected area thoroughly with soap and water. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If symptoms persist or develop, seek medical attention. **Ingestion**-- Do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water. Get medical attention immediately.

Limited Warranty: *Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits.*

For Professional Use

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. OVEREXPOSURE MAY CAUSE CHEMICAL PNEUMONIA,

DELAYED PULMONARY EDEMA AND LUNG CANCER IF INHALED, SKIN DRYNESS OR CRACKING, NARCOTIC EFFECTS AND RESPIRATORY IRRITATION.

